

View Online at <https://aerobasegroup.com/nsn/5945-00-614-1546>

Overall Length:

6.560 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.000 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.093 inches single mounting facility

Overall Height:

4.900 inches

Overall Width:

3.660 inches

Environmental Protection:

Shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.218 inches single mounting facility

Winding Quantity:

2

Coil Quantity:

2

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Features Provided:

Coil voltage suppression and latching contacts

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, double throw, one position momentary

Operating Current Rating And Type:

5.0 amperes dc all windings

Time Delay:

0.025 seconds fixed operate time

Nonpile-up Auxiliary Contact Arrangement:

3 pole, double throw, one position momentary and 2 pole, single throw, normally open, momentary action and 3 pole, single throw, normally closed, momentary action

Auxiliary Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

30.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

225.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load

Special Features:

Aux contact terminals included in connector

Terminal Type And Quantity:

9 threaded stud contacts

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300