NSN 5945-00-619-0755

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-619-0755

Thread Class:

2b second mounting facility

Thread Direction:

Right-hand second mounting facility

Overall Length:

3.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.750 inches second mounting facility

Overall Height:

4.520 inches

Overall Width:

3.090 inches

Case Material:

Plastic

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.199 inches first mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.500 inches second mounting facility

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

6 unthreaded hole first mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

45.392 cubic inches

Thready Qty Per Inch (tpi):

32 second mounting facility

Thread Size:

0.164 inches second mounting facility

NSN 5945-00-619-0755

Electromagnetic Relay - Page 2 of 2



Mounting Facility Pattern:
Rectangular second mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
0.50 seconds adjustable operate time and 5.00 seconds adjustable operate time
Operating Voltage Rating And Type At Specificationified Temp:
28.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
10.0 amperes ac resistive load and 15.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
240.0 ac and 30.0 dc
Energizing Element Power Rating:
8.0 watts
Thread Series Designator:
Unc second mounting facility
Terminal Type And Quantity:
8 screw all functions
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A03300