NSN 5945-00-620-5976

Electromagnetic Relay - Page 1 of 2

14 wire hook all functions



View Online at https://aerobasegroup.com/nsn/5945-00-620-5976

Thread Class:
2a single mounting facility
Overall Length:
1.656 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.938 inches single mounting facility
Overall Height:
2.501 inches
Overall Width:
1.438 inches
Environmental Protection:
Hermetic
Winding Quantity:
1
Coil Quantity:
1
Duty Type:
Continuous
Mounting Facility Type And Quantity:
3 threaded stud single mounting facility
Pile-up Main Contact Form Arrangement:
4c
Thready Qty Per Inch (tpi):
32 single mounting facility
32 Single mounting facility
Thread Size:
Thread Size:
Thread Size: 0.138 inches single mounting facility
Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern:
Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility
Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Operating Current Rating And Type:
Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Operating Current Rating And Type: 250.0 milliamperes dc single winding
Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Operating Current Rating And Type: 250.0 milliamperes dc single winding Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Operating Current Rating And Type: 250.0 milliamperes dc single winding Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.187 inches single mounting facility
Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Operating Current Rating And Type: 250.0 milliamperes dc single winding Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.187 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp:
Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Operating Current Rating And Type: 250.0 milliamperes dc single winding Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.187 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding
Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Operating Current Rating And Type: 250.0 milliamperes dc single winding Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.187 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage:
Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Operating Current Rating And Type: 250.0 milliamperes dc single winding Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.187 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load
Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Operating Current Rating And Type: 250.0 milliamperes dc single winding Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.187 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts:
Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Operating Current Rating And Type: 250.0 milliamperes dc single winding Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.187 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac

NSN 5945-00-620-5976

Electromagnetic Relay - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300