NSN 5945-00-628-6895

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-628-6895

Overall Length:

1.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.437 inches single mounting facility

Overall Height:

1.510 inches

Overall Width:

0.625 inches

Mounting Slot Width:

0.150 inches single mounting facility

Environmental Protection:

Hermetic

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

6840.0 kilohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.015 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

120.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 10.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

NSN 5945-00-628-6895

Electromagnetic Relay - Page 2 of 2

Demilitarization:

No

Fiig:

A03300

