NSN 5945-00-629-1326

Electrical Solenoid - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-00-629-1326

| Center To Center Distance Between Mounting Facilities Parallel To Width: |
|--|
| 0.625 inches |
| Case Material: |
| Steel |
| Case Surface Treatment: |
| Cadmium |
| Environmental Protection: |
| Any acceptable |
| Magnetic Coil Quantity: |
| 1 |
| Electrical Resistance: |
| 2.30 kilohms |
| Voltage Rating In Volts: |
| 140.0 dc |
| Mounting Facility Type And Quantity: |
| 2 threaded hole |
| Current Rating: |
| 0.050 amperes |
| Actuator Stroke Type: |
| Pull and push |
| Linear Force Delivered: |
| 0.08 pounds |
| Power Takeoff Connection Type: |
| Plain-drilled |
| Energizing Stroke Maximum Length: |
| 0.500 inches |
| Thread Size: |
| 0.164 inches mounting facility hole |
| Mounting Facility Pattern: |
| Two position in-line |
| Thread Series Designator: |
| Unc mounting facility hole |
| Terminal Type And Quantity: |
| 2 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A134a0 |