# NSN 5945-00-632-8608

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-632-8608

## **Overall Length:**

1.320 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.078 inches single mounting facility

## **Overall Height:**

0.605 inches

#### **Overall Width:**

0.410 inches

#### **Environmental Protection:**

Hermetic

#### **Unthreaded Mounting Hole Diameter:**

0.120 inches single mounting facility

#### Winding Quantity:

1

#### **Coil Quantity:**

1

#### Winding Dc Resistance Rating:

117.0 ohms single winding and 352.0 ohms single winding

#### **Duty Type:**

Continuous

## Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

### **Features Provided:**

Polarized

#### Mounting Facility Pattern:

In-line single mounting facility

#### Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

#### Time Delay:

0.004 seconds fixed release time

#### **Operating Voltage Rating And Type At Specificationified Temp:**

12.0 volts dc 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes dc resistive load

#### **Test Data Document:**

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Terminal Type And Quantity:**

8 pin all functions

#### **Specification Data:**

81349-mil-r-5757/9 government specification

## Shelf Life:

N/a

# NSN 5945-00-632-8608

Electromagnetic Relay - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300

