NSN 5945-00-655-1498

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-655-1498

| Overall Length: |
|---|
| 3.000 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.625 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.250 inches single mounting facility |
| Overall Height: |
| 2.750 inches |
| Overall Width: |
| 2.000 inches |
| Environmental Protection: |
| Hermetic |
| Unthreaded Mounting Hole Diameter: |
| 0.173 inches single mounting facility |
| Frequency In Hertz: |
| 400.0 |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole single mounting facility |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 4 pole, double throw, one position momentary |
| Operating Current Rating And Type: |
| 200.0 milliamperes ac single winding |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 115.0 volts ac 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 10.0 amperes ac resistive load and 10.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 208.0 ac and 28.0 dc |
| Terminal Type And Quantity: |
| 14 pin all functions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5945-00-655-1498

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300