## NSN 5945-00-655-3146

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-655-3146

**Thread Class:** 

2a single mounting facility

**Overall Length:** 

1.680 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.112 inches single mounting facility

**Overall Diameter:** 

1.110 inches

**Environmental Protection:** 

Hermetic

Winding Quantity:

• • • •

**Coil Quantity:** 

.

Winding Dc Resistance Rating:

700.0 ohms single winding

**Duty Type:** 

Continuous

**Mounting Facility Type And Quantity:** 

2 threaded stud single mounting facility

Thready Qty Per Inch (tpi):

40 single mounting facility

**Thread Size:** 

0.112 inches single mounting facility

**Mounting Facility Pattern:** 

In-line single mounting facility

**Nonpile-up Main Contact Arrangement:** 

3 pole, double throw, one position momentary

Operating Current Rating And Type:

20.0 milliamperes dc single winding

Time Delay:

0.001 seconds fixed operate and release time

**Operating Voltage Rating And Type At Specificationified Temp:** 

37.3 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.5 amperes ac resistive load and 1.5 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

115.0 ac and 26.5 dc

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

11 pin all functions

## NSN 5945-00-655-3146

Electromagnetic Relay - Page 2 of 2



he		

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300