NSN 5945-00-660-6087

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-00-660-6087

| Overall Length: |
|---|
| 1.230 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.000 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.124 inches single mounting facility |
| Overall Height: |
| 1.020 inches |
| Overall Width: |
| 0.400 inches |
| Environmental Protection: |
| Hermetic |
| Unthreaded Mounting Hole Diameter: |
| 0.096 inches single mounting facility |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 552.0 ohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole single mounting facility |
| Pile-up Main Contact Form Arrangement: |
| 2c |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 26.5 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 2.0 amperes ac inductive load and 2.0 amperes dc inductive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A03300 |