# NSN 5945-00-664-6668

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-664-6668

## Thread Class:

2b single mounting facility

## **Thread Direction:**

Right-hand single mounting facility

## **Overall Length:**

2.062 inches

## Center To Center Distance Between Mounting Facilities Parallel To Width:

1.719 inches single mounting facility

### **Overall Height:**

1.562 inches

**Overall Width:** 

2.000 inches

### **Case Material:**

Metal

### **Environmental Protection:**

Hermetic

### **Fragility Factor:**

Moderately rugged

## **Contact Material:**

Silver

## Winding Quantity:

1

## Purpose For Which Designed:

General

### **Coil Quantity:**

1

## Duty Type:

Continuous

Arc Quenching Method:

Air

## Mounting Facility Type And Quantity:

2 threaded hole single mounting facility

### Storage Type:

General purpose warehouse

### Cubic Measure:

6.441 cubic inches

## Thready Qty Per Inch (tpi):

32 single mounting facility

## Thread Size:

0.164 inches single mounting facility

## Mounting Facility Pattern:

In-line single mounting facility

## NSN 5945-00-664-6668

Electromagnetic Relay - Page 2 of 2



Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary **Time Delay:** 10.00 seconds fixed operate time **Operating Voltage Rating And Type At Specificationified Temp:** 120.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.5 amperes ac resistive load and 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 250.0 ac and 50.0 dc **Precious Material And Location:** Contacts silver **Precious Material:** Silver **Thread Series Designator:** Unc single mounting facility **Terminal Type And Quantity:** 8 tab, solder lug all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300