NSN 5945-00-665-7501

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-665-7501

Thread Class:

2a single mounting facility

Overall Length:

1.656 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.562 inches single mounting facility

Overall Diameter:

1.187 inches

Environmental Protection:

Hermetic

Winding Quantity:

Coil Quantity:

.

Winding Dc Resistance Rating:

240.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 threaded stud single mounting facility

Thread Size:

0.138 inches single mounting facility

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

6 pole, double throw, one position momentary

Operating Current Rating And Type:

0.11 amperes dc single winding

Time Delay:

0.01 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 5.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 29.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

20 pin all functions

Shelf Life:

N/a

NSN 5945-00-665-7501

Electromagnetic Relay - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A03300