NSN 5945-00-666-1498

Electromagnetic Relay - Page 1 of 2

Unc single mounting facility



View Online at https://aerobasegroup.com/nsn/5945-00-666-1498

| Thread Class: |
|--|
| 2a single mounting facility |
| Overall Length: |
| 1.620 inches |
| Overall Height: |
| 2.090 inches |
| Overall Width: |
| 1.430 inches |
| Environmental Protection: |
| Hermetic |
| End Application: |
| Type an/slr-2 |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 1.4 kilohms single winding and 1.7 kilohms single winding |
| Duty Type: |
| Intermittent |
| Mounting Facility Type And Quantity: |
| 3 threaded stud single mounting facility |
| Pile-up Main Contact Form Arrangement: |
| 1c |
| Thready Qty Per Inch (tpi): |
| 32 single mounting facility |
| Thread Size: |
| 0.138 inches single mounting facility |
| Mounting Facility Pattern: |
| Triangle single mounting facility |
| Operating Current Rating And Type: |
| 32.0 milliamperes dc single winding |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 1.188 inches single mounting facility |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 48.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 100.0 milliamperes ac resistive load and 100.0 milliamperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 115.0 ac and 250.0 dc |
| Thread Series Designator: |

NSN 5945-00-666-1498

Electromagnetic Relay - Page 2 of 2



| Terminal ' | Type And | Quantity: |
|--------------|------------|------------|
| ı errillinar | I VDE AIIU | Qualitity. |

5 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300