NSN 5945-00-672-4030

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-672-4030

3.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.625 inches single mounting facility

Overall Height:

3.125 inches

Overall Width:

3.130 inches

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.196 inches single mounting facility

Winding Quantity:

2

Coil Quantity:

2

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Features Provided:

Latching contacts

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, double throw, one position momentary

Operating Current Rating And Type:

5.0 amperes dc second winding

Nonpile-up Auxiliary Contact Arrangement:

3 pole, single throw, normally closed, momentary action

Auxiliary Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius second winding

Main Contact Load Current Rating At Maximum Rated Voltage:

60.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac

Terminal Type And Quantity:

19 pin all functions

NSN 5945-00-672-4030

Electromagnetic Relay - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300