## NSN 5945-00-675-2057

Electrical Solenoid - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-00-675-2057

| 3   |
|---|
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.094 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 0.625 inches  |
| Case Material:  |
| Steel   |
| Case Surface Treatment:   |
| Nickel  |
| Environmental Protection:   |
| Any acceptable  |
| Unthreaded Mounting Hole Diameter:  |
| 0.149 inches  |
| Inclosure Type:   |
| Hermetically sealed   |
| Magnetic Coil Quantity:   |
| 1   |
| Electrical Resistance:  |
| 30.000 ohms   |
| Voltage Rating In Volts:  |
| 30.0 dc   |
| Mounting Facility Type And Quantity:                                      |
| 4 unthreaded hole   |
| Current Rating:   |
| 1.000 amperes   |
| Actuator Stroke Type:   |
| Pull and push   |
| Power Takeoff Connection Type:  |
| Internal plunger  |
| Power Takeoff Connection Hole Diameter:                                   |
| 0.040 inches  |
| Mounting Facility Pattern:  |
| Four position rectangular   |
| Terminal Type And Quantity:   |
| 2 wire lead   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |

A134a0