## NSN 5945-00-675-7412

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-675-7412

**Overall Length:** 

**6.250** inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.000 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:** 

4.000 inches single mounting facility

**Overall Height:** 

7.185 inches

**Overall Width:** 

5.063 inches

**Unthreaded Mounting Hole Diameter:** 

0.231 inches single mounting facility

Winding Quantity:

2

**Coil Quantity:** 

2

Winding Dc Resistance Rating:

8.0 ohms all windings

**Duty Type:** 

Continuous

**Mounting Facility Type And Quantity:** 

4 unthreaded hole single mounting facility

**Features Provided:** 

Latching contacts

**Mounting Facility Pattern:** 

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:** 

6 pole, single throw, normally open, momentary action

**Nonpile-up Auxiliary Contact Arrangement:** 

6 pole, single throw, normally open, momentary action and 6 pole, single throw, normally closed, momentary action

**Auxiliary Contact Maximum Voltage Rating In Volts:** 

208.0 ac and 28.0 dc

**Operating Voltage Rating And Type At Specificationified Temp:** 

28.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

175.0 amperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

200.0 ac

**Auxiliary Contact Load Current Rating At Maximum Rated Voltage:** 

6.0 amperes ac resistive load and 6.0 amperes dc resistive load

**Special Features:** 

Coil terminals common to each other

## NSN 5945-00-675-7412

Electromagnetic Relay - Page 2 of 2



Terminal T	ype And	Quantity:
------------	---------	-----------

38 threaded stud all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A03300