

View Online at <https://aerobasegroup.com/nsn/5945-00-675-7412>

Overall Length:

6.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.000 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.000 inches single mounting facility

Overall Height:

7.185 inches

Overall Width:

5.063 inches

Unthreaded Mounting Hole Diameter:

0.231 inches single mounting facility

Winding Quantity:

2

Coil Quantity:

2

Winding Dc Resistance Rating:

8.0 ohms all windings

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Features Provided:

Latching contacts

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

6 pole, single throw, normally open, momentary action

Nonpile-up Auxiliary Contact Arrangement:

6 pole, single throw, normally open, momentary action and 6 pole, single throw, normally closed, momentary action

Auxiliary Contact Maximum Voltage Rating In Volts:

208.0 ac and 28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

175.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

6.0 amperes ac resistive load and 6.0 amperes dc resistive load

Special Features:

Coil terminals common to each other

Terminal Type And Quantity:

38 threaded stud all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A03300