## NSN 5945-00-678-6221

Electromagnetic Relay - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5945-00-678-6221             |
|---|
| Overall Length:   |
| 1.820 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.875 inches single mounting facility                                     |
| Overall Height:   |
| 1.060 inches  |
| Overall Width:  |
| 0.710 inches  |
| Environmental Protection:   |
| Hermetic  |
| Unthreaded Mounting Hole Diameter:  |
| 0.125 inches single mounting facility                                     |
| Frequency In Hertz:   |
| Between 45.0 and 420.0  |
| Winding Quantity:   |
| 1   |
| Coil Quantity:  |
| 1   |
| Winding Dc Resistance Rating:   |
| 8.4 kilohms single winding  |
| Duty Type:  |
| Continuous  |
| Mounting Facility Type And Quantity:                                      |
| 2 unthreaded hole single mounting facility                                |
| Pile-up Main Contact Form Arrangement:                                    |
| 2c  |
| Mounting Facility Pattern:  |
| In-line single mounting facility  |
| Operating Current Rating And Type:  |
| 10.0 milliamperes ac single winding                                       |
| Operating Voltage Rating And Type At Specificationified Temp:             |
| 115.0 volts ac 25 degrees celsius single winding                          |
| Main Contact Load Current Rating At Maximum Rated Voltage:                |
| 2.0 amperes ac resistive load   |
| Main Contact Maximum Voltage Rating In Volts:                             |
| 115.0 ac  |
| Special Features:   |
| Relay incl rectifier single phase, full wave center tap circuit           |
| Terminal Type And Quantity:   |
| 8 pin all functions   |

N/a

Shelf Life:

## NSN 5945-00-678-6221

Electromagnetic Relay - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A03300