

View Online at <https://aerobasegroup.com/nsn/5945-00-681-9449>

**Thread Class:**

2a single mounting facility

**Thread Direction:**

Right-hand single mounting facility

**Overall Length:**

1.359 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.500 inches single mounting facility

**Overall Height:**

2.063 inches

**Overall Width:**

0.984 inches

**Environmental Protection:**

Hermetic

**Contact Material:**

Silver

**Contact Surface Treatment:**

Gold

**End Application:**

Type fa-5530

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

365.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

3 threaded stud single mounting facility

**Pile-up Main Contact Form Arrangement:**

4c

**Thready Qty Per Inch (tpi):**

40 single mounting facility

**Thread Size:**

0.112 inches single mounting facility

**Mounting Facility Pattern:**

Triangle single mounting facility

**Operating Current Rating And Type:**

60.0 milliamperes dc single winding

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

1.000 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:**

24.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

2.0 amperes ac resistive load and 2.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

120.0 ac and 28.0 dc

**Precious Material And Location:**

Contacts silver and contact surfaces gold

**Precious Material:**

Gold and silver

**Thread Series Designator:**

Unc single mounting facility

**Terminal Type And Quantity:**

14 wire hook all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300