

View Online at <https://aerobasegroup.com/nsn/5945-00-681-9716>

Overall Length:

3.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches second mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches second mounting facility

Overall Height:

2.700 inches

Overall Width:

2.300 inches

Case Material:

Metal

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.173 inches second mounting facility

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

6 unthreaded hole second mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

18.630 cubic inches

Mounting Facility Pattern:

Rectangular second mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Operating Current Rating And Type:

500.0 milliamperes dc single winding

Time Delay:

0.025 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac resistive load and 10.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

14 screw all functions

Specification Data:

96906-ms24568 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.