NSN 5945-00-681-9805

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-681-9805 **Thread Class:** 2a single mounting facility **Overall Length:** 0.750 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.220 inches single mounting facility Center To Center Distance Between Mounting Facilities Parallel To Width: 0.488 inches single mounting facility **Overall Height:** 1.075 inches **Overall Width:** 0.714 inches **Environmental Protection:** Hermetic Center To Center Distance Between Mounting Facilities Parallel To Height: 0.488 inches single mounting facility **Winding Quantity:** 2 **Coil Quantity:** Winding Dc Resistance Rating: 4.0 kilohms all windings **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 2 threaded stud single mounting facility **Features Provided:** Polarized and latching contacts Thready Qty Per Inch (tpi): 40 single mounting facility **Thread Size:** 0.112 inches single mounting facility **Mounting Facility Pattern:** Diagonal single mounting facility **Nonpile-up Main Contact Arrangement:** 2 pole, double throw, one position momentary Time Delay: 0.003 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp:

36.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 2.0 amperes dc resistive load

NSN 5945-00-681-9805

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts: 120.0 ac and 30.0 dc Thread Series Designator: Unc single mounting facility Terminal Type And Quantity: 10 wire hook all functions Shelf Life: N/a Unit Of Measure: - Demilitarization:

No Fiig: A03300