

View Online at <https://aerobasegroup.com/nsn/5945-00-681-9805>

Thread Class:

2a single mounting facility

Overall Length:

0.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.220 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.488 inches single mounting facility

Overall Height:

1.075 inches

Overall Width:

0.714 inches

Environmental Protection:

Hermetic

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.488 inches single mounting facility

Winding Quantity:

2

Coil Quantity:

2

Winding Dc Resistance Rating:

4.0 kilohms all windings

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 threaded stud single mounting facility

Features Provided:

Polarized and latching contacts

Thready Qty Per Inch (tpi):

40 single mounting facility

Thread Size:

0.112 inches single mounting facility

Mounting Facility Pattern:

Diagonal single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.003 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

36.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 30.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

10 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiq:

A03300