NSN 5945-00-682-2456

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-682-2456

view Online at https://aerobasegroup.com/nsn/5945-00-662-2456
Overall Length:
4.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.490 inches single mounting facility and 3.510 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.677 inches single mounting facility and 3.697 inches single mounting facility
Overall Height:
5.563 inches
Overall Width:
4.219 inches
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.213 inches single mounting facility and 0.223 inches single mounting facility
Winding Quantity:
1
Coil Quantity:
1
Duty Type:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole single mounting facility
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
3 pole, single throw, normally open, momentary action
Nonpile-up Auxiliary Contact Arrangement:
1 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action
Auxiliary Contact Maximum Voltage Rating In Volts:
28.0 dc
Operating Voltage Rating And Type At Specificationified Temp:
28.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
750.0 milliamperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

416.0 ac

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes dc resistive load

Terminal Type And Quantity:

12 threaded stud all functions

Shelf Life:

N/a

NSN 5945-00-682-2456

Electromagnetic Relay - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A03300