## NSN 5945-00-683-4750

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-683-4750

**Thread Class:** 2a single mounting facility **Thread Direction:** Right-hand single mounting facility **Overall Length:** 1.875 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.562 inches single mounting facility **Overall Height:** 1.750 inches **Overall Width:** 1.312 inches **Environmental Protection:** Hermetic and shock resistant and vibration resistant Winding Quantity: **Coil Quantity: Duty Type:** Continuous **Mounting Facility Type And Quantity:** 2 threaded stud single mounting facility Thready Qty Per Inch (tpi): 48 single mounting facility **Thread Size:** 0.112 inches single mounting facility **Mounting Facility Pattern:** In-line single mounting facility **Nonpile-up Main Contact Arrangement:** 6 pole, double throw, one position momentary Time Delay: 0.015 seconds fixed operate time **Operating Voltage Rating And Type At Specificationified Temp:** 50.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.5 amperes ac resistive load and 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 50.0 dc **Precious Material And Location:** Terminal surfaces gold **Precious Material:** 

Gold

## NSN 5945-00-683-4750

Electromagnetic Relay - Page 2 of 2



| Thread | <b>Series</b> | Design | ator |
|--------|---------------|--------|------|
|        |               |        |      |

Unf single mounting facility

**Terminal Type And Quantity:** 

20 pin all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300