## NSN 5945-00-686-8616

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-686-8616

Thread Class:	
2b single mounting facility	
Thread Direction:	
Right-hand single mounting facility	
Overall Length:	
1.156 inches	
Center To Center Distance Between Mounting Facilities Parallel To Leng	jth:
0.438 inches single mounting facility	
Center To Center Distance Between Mounting Facilities Parallel To Widt	:h:
0.375 inches single mounting facility	
Overall Height:	
1.250 inches	
Overall Width:	
0.688 inches	
Case Material:	
Metal	
Fragility Factor:	
Moderately rugged	
Contact Material:	
Silver	
Winding Quantity:	
1	
Purpose For Which Designed:	
General	
Coil Quantity:	
1	
Winding Dc Resistance Rating:	
280.0 ohms single winding	
Duty Type:	
Continuous	
Arc Quenching Method:	
Air	
Mounting Facility Type And Quantity:	
4 threaded hole single mounting facility	
Storage Type:	
General purpose warehouse	
Cubic Measure:	
0.994 cubic inches	
Thready Qty Per Inch (tpi):	
40 single mounting facility	
Thread Size:	
0.112 inches single mounting facility	

## NSN 5945-00-686-8616

Electromagnetic Relay - Page 2 of 2



**Mounting Facility Pattern:** Rectangular single mounting facility Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary **Time Delay:** 0.015 seconds fixed operate time **Operating Voltage Rating And Type At Specificationified Temp:** 28.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 3.0 amperes ac resistive load and 3.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 26.5 dc **Precious Material And Location:** Contacts silver **Precious Material:** Silver **Thread Series Designator:** Unc single mounting facility **Terminal Type And Quantity:** 14 tab, solder lug all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300