NSN 5945-00-688-2398

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-688-2398

Inread Class:
2b single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
1.688 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.875 inches single mounting facility
Overall Height:
1.344 inches
Overall Width:
0.953 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
365.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 threaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
2.162 cubic inches
Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:

0.138 inches single mounting facility

NSN 5945-00-688-2398

Electromagnetic Relay - Page 2 of 2



Mounting Facility Pattern: In-line single mounting facility **Nonpile-up Main Contact Arrangement:** 4 pole, double throw, one position momentary Time Delay: 0.015 seconds fixed operate time **Operating Voltage Rating And Type At Specificationified Temp:** 28.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 3.0 amperes ac resistive load and 3.0 amperes dc resistive load **Main Contact Maximum Voltage Rating In Volts:** 115.0 ac and 26.5 dc **Precious Material And Location:** Contacts silver **Precious Material:** Silver **Thread Series Designator:** Unc single mounting facility **Terminal Type And Quantity:** 14 pin all functions Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A03300