NSN 5945-00-695-2629

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-695-2629

| view Online at https://aerobasegroup.com/hsh/5945-00-695-2629 |
|---|
| Overall Length: |
| 13.200 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 13.250 inches single mounting facility |
| Overall Height: |
| 10.000 inches |
| Overall Width: |
| 7.150 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.406 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 8.500 inches single mounting facility |
| Frequency In Hertz: |
| 60.0 |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 2.20 ohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole single mounting facility |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 3 pole, single throw, normally open, momentary action |
| Operating Current Rating And Type: |
| 1.35 amperes ac single winding |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 208.0 volts ac 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 115.0 amperes ac resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 440.0 ac |
| Terminal Type And Quantity: |
| 8 pin all functions |

Fsc Application Data (non-core):

Control panel group, generator set

NSN 5945-00-695-2629

Electromagnetic Relay - Page 2 of 2



| - | | | | | |
|---|----|----|----|---|---|
| • | he | 1+ | 18 | Δ | • |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300