# NSN 5945-00-700-3413

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-700-3413

Overall Length:	
1.180 inches	
Center To Center Distance Between Mounting Facili	ties Parallel To Length:
1.000 inches single mounting facility	
Center To Center Distance Between Mounting Facili	ties Parallel To Width:
0.125 inches single mounting facility	
Overall Height:	
1.020 inches	
Overall Width:	
0.400 inches	
Case Material:	
Metal	
Environmental Protection:	
Hermetic	
Unthreaded Mounting Hole Diameter:	
0.096 inches single mounting facility	
Fragility Factor:	
Moderately rugged	
Contact Material:	
Silver	
Contact Surface Treatment:	
Gold	
Winding Quantity:	
1	
Purpose For Which Designed:	
General	
Coil Quantity:	
1	
Winding Dc Resistance Rating:	
600.0 ohms single winding	
Duty Type:	
Continuous	
Arc Quenching Method:	
Air	
Mounting Facility Type And Quantity:	
2 unthreaded hole single mounting facility	
Storage Type:	
General purpose warehouse	
Cubic Measure:	
0.481 cubic inches	
Mounting Facility Pattern:	
Diagonal single mounting facility	

# NSN 5945-00-700-3413

Electromagnetic Relay - Page 2 of 2



## **Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

# **Operating Current Rating And Type:**

21.0 milliamperes dc single winding

## Time Delay:

0.005 seconds fixed operate and release time

# **Operating Voltage Rating And Type At Specificationified Temp:**

26.0 volts dc 25 degrees celsius single winding

## Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 2.0 amperes dc resistive load

#### Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### **Precious Material And Location:**

Contacts silver and contact surfaces gold

#### **Precious Material:**

Silver and gold

## **Terminal Type And Quantity:**

8 wire hook all functions

Shelf Life:

N/a

**Unit Of Measure:** 

# Demilitarization:

No

Fiig:

A03300