## NSN 5945-00-708-7571

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-708-7571

**Thread Class:** 

2a single mounting facility

**Thread Direction:** 

Right-hand single mounting facility

**Overall Length:** 

2.070 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:** 

1.312 inches single mounting facility

**Overall Height:** 

3.390 inches

**Overall Width:** 

2.070 inches

**Environmental Protection:** 

Shock resistant and vibration resistant

**Winding Quantity:** 

1

**Coil Quantity:** 

.

Winding Dc Resistance Rating:

92.0 ohms single winding

**Duty Type:** 

Continuous

**Mounting Facility Type And Quantity:** 

4 threaded stud single mounting facility

**Features Provided:** 

Coil voltage suppression

**Cubic Measure:** 

14.525 cubic inches

Thready Qty Per Inch (tpi):

32 single mounting facility

**Thread Size:** 

0.164 inches single mounting facility

**Mounting Facility Pattern:** 

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:** 

4 pole, double throw, one position momentary

Time Delay:

0.05 seconds fixed release time

**Operating Voltage Rating And Type At Specificationified Temp:** 

26.0 volts dc 25 degrees celsius single winding

## NSN 5945-00-708-7571

Electromagnetic Relay - Page 2 of 2



## Main Contact Load Current Rating At Maximum Rated Voltage:

16.0 amperes ac resistive load and 16.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

115.0 ac and 28.0 dc

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

14 screw all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300