

View Online at <https://aerobasegroup.com/nsn/5945-00-708-7571>

**Thread Class:**

2a single mounting facility

**Thread Direction:**

Right-hand single mounting facility

**Overall Length:**

2.070 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.375 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.312 inches single mounting facility

**Overall Height:**

3.390 inches

**Overall Width:**

2.070 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

92.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 threaded stud single mounting facility

**Features Provided:**

Coil voltage suppression

**Cubic Measure:**

14.525 cubic inches

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.164 inches single mounting facility

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

**Time Delay:**

0.05 seconds fixed release time

**Operating Voltage Rating And Type At Specificationified Temp:**

26.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

16.0 amperes ac resistive load and 16.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Thread Series Designator:**

Unc single mounting facility

**Terminal Type And Quantity:**

14 screw all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300