## NSN 5945-00-722-1438

Electromagnetic Relay - Page 1 of 2

**Overall Length:** 



View Online at https://aerobasegroup.com/nsn/5945-00-722-1438

| 1.840 inches  |
|---|
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.562 inches single mounting facility                                     |
| Overall Height:   |
| 2.346 inches  |
| Overall Width:  |
| 1.320 inches  |
| Case Material:  |
| Metal   |
| Environmental Protection:   |
| Hermetic  |
| Unthreaded Mounting Hole Diameter:  |
| 0.144 inches single mounting facility                                     |
| Fragility Factor:   |
| Moderately rugged   |
| Winding Quantity:   |
| 1   |
| Purpose For Which Designed:   |
| General   |
| Coil Quantity:  |
| 1   |
| Duty Type:  |
| Continuous  |
| Arc Quenching Method:   |
| Air   |
| Mounting Facility Type And Quantity:                                      |
| 2 unthreaded hole single mounting facility                                |
| Storage Type:   |
| General purpose warehouse   |
| Cubic Measure:  |
| 5.698 cubic inches  |
| Mounting Facility Pattern:  |
| In-line single mounting facility  |
| Nonpile-up Main Contact Arrangement:                                      |
| 4 pole, double throw, one position momentary                              |
| Operating Current Rating And Type:  |
| 36.0 milliamperes dc single winding                                       |
| Time Delay:   |
| 0.05 seconds fixed release time   |
| Operating Voltage Rating And Type At Specificationified Temp:             |
| 115.0 volts ac 25 degrees celsius single winding                          |
|   |

## NSN 5945-00-722-1438

Electromagnetic Relay - Page 2 of 2



## Main Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes ac resistive load and 3.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

115.0 ac and 30.0 dc

**Terminal Type And Quantity:** 

14 wire hook all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300