NSN 5945-00-722-7616

Electromagnetic Relay - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5945-00-722-7616 |
|---|
| Thread Class: |
| 2a single mounting facility |
| Overall Length: |
| 1.960 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.562 inches single mounting facility |
| Overall Height: |
| 1.350 inches |
| Overall Width: |
| 1.880 inches |
| Environmental Protection: |
| Hermetic |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 170.0 ohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Inert gas |
| Mounting Facility Type And Quantity: |
| 2 threaded stud single mounting facility |
| Pile-up Main Contact Form Arrangement: |
| 6c |
| Thread Size: |
| 0.138 inches single mounting facility |
| Mounting Facility Pattern: |
| In-line single mounting facility |
| Operating Current Rating And Type: |
| 155.0 milliamperes dc single winding |
| Time Delay: |
| 0.025 seconds fixed operate time |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 26.5 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 2.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 26.5 dc |

Thread Series Designator:

Unc single mounting facility

NSN 5945-00-722-7616

Electromagnetic Relay - Page 2 of 2



| T | erm | inal | Type | Δnd | Ou | antity | ,. |
|---|-------|-------|------|------|----|--------|----|
| ı | GIIII | ıııaı | IVDE | Allu | чu | annını | |

20 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300