NSN 5945-00-725-7502

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-725-7502

Thread Class:
2b single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
1.562 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches single mounting facility
Overall Height:
1.469 inches
Overall Width:
1.031 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.438 inches single mounting facility
Fragility Factor:
Moderately rugged
Frequency In Hertz:
requested in richtz.
60.0
60.0
60.0 Winding Quantity:
60.0 Winding Quantity: 1
60.0 Winding Quantity: 1 Purpose For Which Designed:
60.0 Winding Quantity: 1 Purpose For Which Designed: General
Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity:
Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1
Winding Quantity: Purpose For Which Designed: General Coil Quantity: Winding Dc Resistance Rating:
Winding Quantity: Purpose For Which Designed: General Coil Quantity: Winding Dc Resistance Rating: 8.4 kilohms single winding
Winding Quantity: Purpose For Which Designed: General Coil Quantity: Winding Dc Resistance Rating: 8.4 kilohms single winding Duty Type:
Winding Quantity: Purpose For Which Designed: General Coil Quantity: Winding Dc Resistance Rating: 8.4 kilohms single winding Duty Type: Continuous
Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 8.4 kilohms single winding Duty Type: Continuous Arc Quenching Method:
Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 8.4 kilohms single winding Duty Type: Continuous Arc Quenching Method: Air
Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 8.4 kilohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity:
Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 8.4 kilohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 threaded hole single mounting facility
Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 8.4 kilohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 threaded hole single mounting facility Storage Type:
Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 8.4 kilohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 threaded hole single mounting facility Storage Type: General purpose warehouse

40 single mounting facility

NSN 5945-00-725-7502

Electromagnetic Relay - Page 2 of 2



T	h	re	a	d	S	iz	e:	

0.112 inches single mounting facility

Mounting Facility Pattern:

Diagonal single mounting facility

Nonpile-up Main Contact Arrangement:

5 pole, single throw, normally open, momentary action

Time Delay:

0.05 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

12 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300