# NSN 5945-00-729-7014

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-729-7014

## Overall Length:

6.885 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

6.875 inches single mounting facility

## Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility

### **Overall Height:**

4.125 inches

#### **Overall Width:**

3.468 inches

**Case Material:** 

Metal

**Unthreaded Mounting Hole Diameter:** 

0.266 inches single mounting facility

#### **Fragility Factor:**

Moderately rugged

# Winding Quantity:

2

## **Purpose For Which Designed:**

General

## Coil Quantity:

2

### Winding Dc Resistance Rating:

41.0 ohms single winding

### **Duty Type:**

Continuous

### Arc Quenching Method:

Air

## Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

## Storage Type:

General purpose warehouse

## **Cubic Measure:**

98.493 cubic inches

## Mounting Facility Pattern:

Diamond single mounting facility

## Nonpile-up Main Contact Arrangement:

4 pole, single throw, normally open, double make, momentary action

## Time Delay:

0.045 seconds fixed operate time

## Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

NSN 5945-00-729-7014

Electromagnetic Relay - Page 2 of 2



#### Main Contact Load Current Rating At Maximum Rated Voltage:

150.0 amperes ac resistive load and 200.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

## **Test Data Document:**

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

12 threaded stud all functions

#### **Specification Data:**

96906-ms25032 government standard

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.