NSN 5945-00-732-9538

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-732-9538

Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
0.800 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.412 inches single mounting facility
Overall Height:
1.432 inches
Overall Width:
0.400 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
1.2 kilohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
2 threaded stud single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.458 cubic inches
Thready Qty Per Inch (tpi):
40 single mounting facility
Thread Size:
0.112 inches single mounting facility

Mounting Facility Pattern: In-line single mounting facility

NSN 5945-00-732-9538

Electromagnetic Relay - Page 2 of 2



Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

Operating Current Rating And Type:

10.5 milliamperes dc single winding

Time Delay:

0.006 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

26.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 3.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material And Location:

Contacts silver and contact surfaces gold

Precious Material:

Silver and gold

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

5 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300