## NSN 5945-00-735-1837

Meter Movement Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-735-1837

Terminal Quantity:
5
Terminal Type:
Threaded stud
Case Material:
Plastic
End Application:
Type no; rtc-2
Mounting Configuration:
Four 0.112 in. Diameter mtg holes on 2.250 in. Mtg centers
Voltage Rating:
60.0 volts
Scale Measurement Range:
+2300.0/+3100.0
Main Contact Arrangement:
1 pole, single throw, normally open, momentary action
Main Contact Current Type:
Dc
Main Contact Current Rating:
6.0 milliamperes
Meter Movement Current Type:
Dc
Meter Movement Voltage In Volts:
0.100
Meter Movement Current Range:
+0.0/+100.0 microamperes
Meter Mounting Type:
Flush
Contact Closing Condition:
Increase value
Reset Facility Feature:
Provided
Lock In Device Type:
Coil
Release Method:
Deenergize lock-in coil
Meter Depth Behind Mounting Flange:
2.015 inches
2.015 inches  Mounting Flange Diameter:

2.800 inches

## NSN 5945-00-735-1837

Meter Movement Relay - Page 2 of 2



Special	Features:
---------	-----------

Swuitter rate pps - fs equals 100 ua dc marked on meter face

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T142-k