NSN 5945-00-735-1837

Meter Movement Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-735-1837

| Terminal Quantity: |
|------------------------------------------------------------|
| 5 |
| Terminal Type: |
| Threaded stud |
| Case Material: |
| Plastic |
| End Application: |
| Type no; rtc-2 |
| Mounting Configuration: |
| Four 0.112 in. Diameter mtg holes on 2.250 in. Mtg centers |
| Voltage Rating: |
| 60.0 volts |
| Scale Measurement Range: |
| +2300.0/+3100.0 |
| Main Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action |
| Main Contact Current Type: |
| Dc |
| Main Contact Current Rating: |
| 6.0 milliamperes |
| Meter Movement Current Type: |
| Dc |
| Meter Movement Voltage In Volts: |
| 0.100 |
| Meter Movement Current Range: |
| +0.0/+100.0 microamperes |
| Meter Mounting Type: |
| Flush |
| Contact Closing Condition: |
| Increase value |
| Reset Facility Feature: |
| Provided |
| Lock In Device Type: |
| Coil |
| Release Method: |
| Deenergize lock-in coil |
| Meter Depth Behind Mounting Flange: |
| |
| 2.015 inches |
| 2.015 inches Mounting Flange Diameter: |
| |

2.800 inches

NSN 5945-00-735-1837

Meter Movement Relay - Page 2 of 2



| Special | Features: |
|---------|-----------|
|---------|-----------|

Swuitter rate pps - fs equals 100 ua dc marked on meter face

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T142-k