NSN 5945-00-754-7276

Electromagnetic Relay - Page 1 of 2

Overall Length: 3.640 inches



View Online at https://aerobasegroup.com/nsn/5945-00-754-7276

Center To Center Distance Between Mounting Facilities Parallel To Width:

_
2.615 inches single mounting facility
Overall Height:
3.250 inches
Overall Width:
2.925 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.266 inches single mounting facility
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
64.5 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
34.602 cubic inches
Mounting Facility Pattern:
In-line single mounting facility
Nonpile-up Main Contact Arrangement:
1 pole, single throw, normally open, double make, momentary action
Time Delay:
0.02 seconds fixed operate time
Operating Voltage Rating And Type At Specificationified Temp:
28.0 volts dc 25 degrees celsius single winding

NSN 5945-00-754-7276

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 amperes ac resistive load and 100.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 threaded stud all functions

Specification Data:

96906-ms24141 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.