## NSN 5945-00-755-4315

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-755-4315

Thread Class:						
2a single mounting facility						
Overall Length:						
2.060 inches						
Overall Height:						
0.980 inches						
Overall Width:						
1.350 inches						
Environmental Protection:						
Hermetic						
Winding Quantity:						
1						
Coil Quantity:						
1						
Winding Dc Resistance Rating:						
360.0 ohms single winding						
Duty Type:						
Continuous						
Mounting Facility Type And Quantity:						
3 threaded stud single mounting facility						
Pile-up Main Contact Form Arrangement:						
3c						
Thready Qty Per Inch (tpi):						
40 single mounting facility						
Thread Size:						
0.112 inches single mounting facility						
0.112 inches single mounting facility  Mounting Facility Pattern:						
Mounting Facility Pattern:						
Mounting Facility Pattern:  Triangle single mounting facility						
Mounting Facility Pattern:  Triangle single mounting facility  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:						
Mounting Facility Pattern:  Triangle single mounting facility  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.000 inches single mounting facility						
Mounting Facility Pattern:  Triangle single mounting facility  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.000 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:						
Mounting Facility Pattern:  Triangle single mounting facility  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.000 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  28.0 volts dc 25 degrees celsius single winding						
Mounting Facility Pattern:  Triangle single mounting facility  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.000 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  28.0 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:						
Mounting Facility Pattern:  Triangle single mounting facility  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.000 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  28.0 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  2.5 amperes ac resistive load						
Mounting Facility Pattern:  Triangle single mounting facility  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.000 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  28.0 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  2.5 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:						
Mounting Facility Pattern:  Triangle single mounting facility  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.000 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  28.0 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  2.5 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:  117.0 ac						
Mounting Facility Pattern:  Triangle single mounting facility  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.000 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  28.0 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  2.5 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:  117.0 ac  Thread Series Designator:						
Mounting Facility Pattern:  Triangle single mounting facility  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.000 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  28.0 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  2.5 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:  117.0 ac  Thread Series Designator:  Unc single mounting facility						
Mounting Facility Pattern: Triangle single mounting facility Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.000 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.5 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 117.0 ac Thread Series Designator: Unc single mounting facility Terminal Type And Quantity:						

## NSN 5945-00-755-4315

Electromagnetic Relay - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A03300