

View Online at <https://aerobasegroup.com/nsn/5945-00-755-4778>

Overall Length:

4.343 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.677 inches single mounting facility and 3.697 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.490 inches single mounting facility and 3.510 inches single mounting facility

Overall Height:

3.956 inches

Overall Width:

4.156 inches

Unthreaded Mounting Hole Diameter:

0.218 inches single mounting facility

Frequency In Hertz:

400.0

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, double make, momentary action

Operating Current Rating And Type:

200.0 milliamperes ac single winding

Nonpile-up Auxiliary Contact Arrangement:

1 two circuit, double break/double make, one position momentary

Auxiliary Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 amperes ac resistive load and 150.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

416.0 ac and 28.0 dc

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac motor load and 5.0 amperes dc motor load

Terminal Type And Quantity:

12 threaded stud all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300