

View Online at <https://aerobasegroup.com/nsn/5945-00-755-4778>

**Overall Length:**

4.343 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.677 inches single mounting facility and 3.697 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.490 inches single mounting facility and 3.510 inches single mounting facility

**Overall Height:**

3.956 inches

**Overall Width:**

4.156 inches

**Unthreaded Mounting Hole Diameter:**

0.218 inches single mounting facility

**Frequency In Hertz:**

400.0

**Winding Quantity:**

1

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

3 pole, single throw, normally open, double make, momentary action

**Operating Current Rating And Type:**

200.0 milliamperes ac single winding

**Nonpile-up Auxiliary Contact Arrangement:**

1 two circuit, double break/double make, one position momentary

**Auxiliary Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Operating Voltage Rating And Type At Specificationified Temp:**

115.0 volts ac 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

100.0 amperes ac resistive load and 150.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

416.0 ac and 28.0 dc

**Auxiliary Contact Load Current Rating At Maximum Rated Voltage:**

5.0 amperes ac motor load and 5.0 amperes dc motor load

**Terminal Type And Quantity:**

12 threaded stud all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300