

View Online at <https://aerobasegroup.com/nsn/5945-00-759-1415>

Thread Class:

2a single mounting facility

Overall Length:

3.062 inches

Overall Height:

1.750 inches

Overall Width:

2.593 inches

Case Material:

Steel, corrosion resisting

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.990 inches single mounting facility and 1.010 inches single mounting facility

Fragility Factor:

Moderately rugged

Frequency In Hertz:

400.0

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

6.0 kilohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

3 threaded stud single mounting facility

Cubic Measure:

13.895 cubic inches

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

20.0 milliamperes ac single winding

Time Delay:

4.50 seconds fixed operate and release time and 5.50 seconds fixed operate and release time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.740 inches single mounting facility and 1.760 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

120.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 3.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 wire hook all functions

Fsc Application Data:

Radar set, antps43b, german tactical air defense system, tads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300