

View Online at <https://aerobasegroup.com/nsn/5945-00-761-5679>

Overall Length:

4.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility

Overall Height:

4.030 inches

Overall Width:

4.000 inches

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.196 inches single mounting facility

Winding Quantity:

2

Coil Quantity:

2

Winding Dc Resistance Rating:

36.0 ohms all windings

Duty Type:

Intermittent

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Features Provided:

Latching contacts

Mounting Facility Pattern:

Rectangular single mounting facility

Operating Current Rating And Type:

600.0 milliamperes dc all windings

Time Delay:

180.00 seconds fixed operate time

Nonpile-up Auxiliary Contact Arrangement:

1 pole, single throw, normally open, momentary action and 1 pole, double throw, one position momentary

Auxiliary Contact Maximum Voltage Rating In Volts:

28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

600.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

29.0 dc

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes dc resistive load

Special Features:

One terminal common to one auxiliary contact and coil; negative terminal common to both coils

Terminal Type And Quantity:

8 threaded stud all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300