NSN 5945-00-761-5820



Electromagnetic Relay - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5945-00-761-5820
Overall Length:
2.187 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.750 inches single mounting facility
Overall Height:
1.124 inches
Overall Width:
1.490 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.147 inches single mounting facility
Fragility Factor:

Moderately rugged

Winding Quantity:

Purpose For Which Designed:

General

Coil Quantity:

- -

Winding Dc Resistance Rating:

480.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

3 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

3.662 cubic inches

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Operating Current Rating And Type:

134.0 milliamperes dc single winding

Time Delay:

0.02 seconds fixed operate and release time

NSN 5945-00-761-5820

Electromagnetic Relay - Page 2 of 2



Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.844 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

48.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Terminal Type And Quantity:

14 pin all functions

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A03300