# NSN 5945-00-761-5821

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-761-5821

## Overall Length:

2.187 inches

## Center To Center Distance Between Mounting Facilities Parallel To Width:

0.750 inches single mounting facility

## **Overall Height:**

1.124 inches

## **Overall Width:**

1.490 inches

#### **Case Material:**

Metal

#### **Environmental Protection:**

Hermetic

## **Unthreaded Mounting Hole Diameter:**

0.147 inches single mounting facility

#### **Fragility Factor:**

## Moderately rugged

Frequency In Hertz:

400.0

## Winding Quantity:

1

## **Purpose For Which Designed:**

General

## **Coil Quantity:**

1

## Duty Type:

Continuous

## Arc Quenching Method:

Air

## Mounting Facility Type And Quantity:

3 unthreaded hole single mounting facility

## Storage Type:

General purpose warehouse

## **Cubic Measure:**

3.662 cubic inches

## Mounting Facility Pattern:

Triangle single mounting facility

## Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

## Operating Current Rating And Type:

73.0 milliamperes ac single winding

## Time Delay:

0.02 seconds fixed operate and release time

## NSN 5945-00-761-5821

Electromagnetic Relay - Page 2 of 2



## Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.844 inches single mounting facility

#### **Operating Voltage Rating And Type At Specificationified Temp:**

115.0 volts ac 25 degrees celsius single winding

## Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### **Terminal Type And Quantity:**

14 pin all functions

Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A03300