NSN 5945-00-764-0366

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-764-0366

Overall Length:

3.730 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.305 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.865 inches single mounting facility

Overall Height:

2.438 inches

Overall Width:

3.305 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.218 inches single mounting facility

Winding Quantity:

1

Coil Quantity:

Winding Dc Resistance Rating:

50.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

Operating Current Rating And Type:

640.0 milliamperes dc single winding

Time Delay:

0.025 seconds fixed operate time

Nonpile-up Auxiliary Contact Arrangement:

1 two circuit, both positions maintained

Auxiliary Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

50.0 amperes ac resistive load and 50.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

NSN 5945-00-764-0366

Electromagnetic Relay - Page 2 of 2



Terminal Type Ar	nd Quantity:
------------------	--------------

12 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300