

View Online at <https://aerobasegroup.com/nsn/5945-00-765-5347>

**Thread Class:**

2a mounting facility stud

**Thread Direction:**

Right-hand mounting facility stud

**Body Style:**

Armature end actuator

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.250 inches

**Body Diameter:**

1.875 inches

**Body Height:**

2.254 inches

**Environmental Protection:**

Corrosion resistant and fungus resistant and humidity resistant and salt spray resistant and vibration resistant

**Maximum Operating Temp:**

80.0 degrees celsius

**Actuator Length:**

0.562 inches

**Fragility Factor:**

Moderately rugged

**Actuator Diameter:**

0.156 inches

**Inclosure Type:**

Fully enclosed

**Magnetic Coil Quantity:**

1

**Electrical Resistance:**

10.30 ohms

**Duty Type:**

Continuous

**Terminal Location:**

Circumference

**Voltage Rating In Volts:**

28.0 dc

**Mounting Facility Type And Quantity:**

2 threaded stud

**Torque Rating And Type:**

7.00 inch-pounds starting

**Cubic Measure:**

6.639 cubic inches

**Thready Qty Per Inch (tpi):**

32 mounting facility stud

**Actuator Stroke Type:**

Rotary

**Power Takeoff Connection Type:**

Plain

**Energizing Stroke Maximum Length:**

0.042 inches

**Thread Size:**

0.164 inches mounting facility stud

**Mounting Facility Pattern:**

Two position in-line

**Rotation Direction And Energizing Stroke In Angular Deg:**

12.0 counterclockwise

**Thread Series Designator:**

Unc mounting facility stud

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A134a0