NSN 5945-00-767-0083

Reed Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-767-0083

| Overall Length: |
|---|
| 1.125 inches |
| Overall Height: |
| 0.620 inches |
| Overall Width: |
| 0.530 inches |
| Environmental Protection: |
| Dustproof |
| Fragility Factor: |
| Moderately rugged |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 2.5 kilohms single winding and 3.1 kilohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 1 plug-in terminal single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Features Provided: |
| Electrostatic shield and magnetic shield |
| Cubic Measure: |
| 0.370 cubic inches |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, double throw, one position momentary |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 24.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 250.0 milliamperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Energizing Element Power Rating: |
| 3.0 watts |
| Terminal Type And Quantity: |
| 8 pin all functions |
| Shelf Life: |
| N/a |

NSN 5945-00-767-0083

Reed Relay - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A03300