

View Online at <https://aerobasegroup.com/nsn/5945-00-773-3392>

Overall Length:

4.630 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.000 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.500 inches single mounting facility

Overall Height:

3.880 inches

Overall Width:

5.060 inches

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.196 inches single mounting facility

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

92.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

Nonpile-up Auxiliary Contact Arrangement:

1 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action and 1 pole, double throw, one position momentary

Auxiliary Contact Maximum Voltage Rating In Volts:

28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

200.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

208.0 ac

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes dc resistive load

Special Features:

Automatic integral switch opens to cut-in second winding to increase resistance for holding

Terminal Type And Quantity:

12 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300