

View Online at <https://aerobasegroup.com/nsn/5945-00-773-3860>

Overall Length:

6.688 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.000 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility

Overall Height:

3.750 inches

Overall Width:

3.000 inches

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.266 inches single mounting facility

Winding Quantity:

2

Coil Quantity:

2

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Diamond single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Time Delay:

0.035 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

75.0 amperes ac resistive load and 100.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

12 screw all functions

Specification Data:

96906-ms25031 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-prf-6106 spec.