## NSN 5945-00-782-7277

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-00-782-7277

Length:

| Overall Length:   |
|---|
| 1.310 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To |
| 0.531 inches single mounting facility                             |
| Overall Diameter:   |
| 1.060 inches  |
| Environmental Protection:   |
| Hermetic  |
| Unthreaded Mounting Hole Diameter:                                |
| 0.171 inches single mounting facility                             |
| Frequency In Hertz:   |
| 400.0   |
| Winding Quantity:   |
| 1   |
| Coil Quantity:  |
| 1   |
| Winding Dc Resistance Rating:                                     |
| 5.000 kilohms single winding                                      |
| Duty Type:  |
| Continuous  |
| Mounting Facility Type And Quantity:                              |
| 2 unthreaded hole single mounting facility                        |
| Mounting Facility Pattern:  |
| In-line single mounting facility                                  |
| Operating Voltage Rating And Type At Specificationified Temp:     |
| 115.0 volts ac 25 degrees celsius single winding                  |
| Main Contact Load Current Rating At Maximum Rated Voltage:        |
| 5.0 amperes ac inductive load and 10.0 amperes dc inductive load  |
| Main Contact Maximum Voltage Rating In Volts:                     |
| 115.0 ac and 30.0 dc  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A03300  |
|   |